

ja-netfilter v2.2.2

A javaagent framework

Usage

- download from the [releases page](#)
- add `-javaagent:/absolute/path/to/ja-netfilter.jar` argument (**Change to your actual path**)
 - add as an argument of the `java` command. eg:
`java -javaagent:/absolute/path/to/ja-netfilter.jar -jar executable_jar_file.jar`
 - some apps support the `JVM Options file`, you can add as a line of the `JVM Options file`.
 - **WARNING: DO NOT put some unnecessary whitespace characters!**
- or execute `java -jar /path/to/ja-netfilter.jar` to use `attach mode`.
- edit your plugin config files: `${lower plugin name}.conf` file in the `config` dir where `ja-netfilter.jar` is located.
- the `config`, `logs` and `plugins` directories can be specified through **the javaagent args**.
 - eg: `-javaagent:/path/to/ja-netfilter.jar=appName`, your config, logs and plugins directories will be `config-appname`, `logs-appname` and `plugins-appname`.
 - if no javaagent args, they default to `config`, `logs` and `plugins`.
 - this mechanism will avoid extraneous and bloated `config`, `logs` and `plugins`.
- run your java application and enjoy~

Config file format

```
[ABC]
# for the specified section name

# for example
[URL]
EQUAL,https://someurl

[DNS]
EQUAL,somedomain

# EQUAL      Use `equals` to compare
# EQUAL_IC   Use `equals` to compare, ignore case
# KEYWORD    Use `contains` to compare
# KEYWORD_IC Use `contains` to compare, ignore case
# PREFIX     Use `startsWith` to compare
# PREFIX_IC  Use `startsWith` to compare, ignore case
# SUFFIX     Use `endsWith` to compare
# SUFFIX_IC  Use `endsWith` to compare, ignore case
# REGEXP     Use regular expressions to match
```

Debug info

- the `ja-netfilter` will **NOT** output debugging information by default
- add environment variable `JANF_DEBUG=1` (log level) and start to enable it
- or add system property `-Djanf.debug=1` (log level) to enable it
- log level: `NONE=0` , `DEBUG=1` , `INFO=2` , `WARN=3` , `ERROR=4`

Plugin system

- for developer:
 - view the [scaffold project](#) written for the plugin system
 - compile your plugin and publish it
 - just use your imagination~
- for user:
 - download the jar file of the plugin
 - put it in the subdirectory called `plugins` where the `ja-netfilter.jar` file is located
 - enjoy the new capabilities brought by the plugin
 - if the file suffix is `.disabled.jar` , the plugin will be disabled